



**NOTE:**  
**1. MATERIAL:**  
 a. HOUSING: PBTVO+GF BK  
 b. CONTACT: C2880  
 (SURFACE PLATING: Sn 100u")  
**2. ELECTRIC:**  
 a. CONTACT RESISTANCE: 30 MILLIOHMS MAX  
 b. INSULATION RESISTANCE: 1000 MEGA OHMS MIN  
 c. DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL  
 d. OPERATING TEMPERATURE: -55°C TO 105°C

GS073A - 02 1 1

BATTERY DIM  
 Ø2: D=23.8mm  
 T=5.0mm

COLOR: 1: BLACK

PLATING  
 1: Sn 100u" MIN  
 OVER 50u" MIN NICKEL  
 G: LEAD-FREE

**PCB HOLE LAYOUT**

UNIT: mm

**NOTES**  
**CUSTOMER DRAWING**



General Tolerances: Mgr: ±0.25		Date: 10/09/14		Sheet: 1 OF 1	
Dim: 0.0 ±0.25		Drawn by:		REV: A	
0.00 ±0.20		CHK'd by:		Dwg. NO: GS073A-021G	
0.000 ±0.10		Scale: 1 : 1		Title: BATTERY HOLDER	
REV	Revision Record	Date	Appr'd by	Scale	Title
A	RELEASE	10/09/14		1 : 1	BATTERY HOLDER
Revise Only Dr. Cad System					