

NOTES:

1. BASE:
MAT'L: PBT V0+GF BLACK
2. CONTACTS:
MAT'L: C2680
3. ELECTRIC:
 - a. CONTACT RESISTANCE: 30 MILLIOHMS MAX
 - b. INSULATION RESISTANCE: 1000 MEGA OHMS MIN
 - c. DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL
 - d. OPERATING TEMPERATURE: -55°C-105°C


GS075A - 02 1 X

BATTERY DIM

02:D=19.8mm
T=3.2mm

COLOR: 1:BLACK
PLATING 1:Sn/Pb 90/10 100u" MIN
OVER 50u" MIN NICKEL
GLEAD-FREE

PCB HOLE LAYOUT



SECTION A-A

<p>NOTES</p> <p>CUSTOMER DRAWING</p>		Date: 12/12/014	
		Drawn by	Appr'd by
<p>General Tolerances: Dim 0.00 ±0.5 Angle 0° ±1°</p> <p>Scale 1 : 1</p>		<p>CHK'd by</p> <p>Scale 1 : 1</p>	
<p>Global Shine Technology Co., Ltd. TEL:8200-3005 FAX:8200-3014</p>		<p>Date: 12/12/014 Sheet 1 OF 1</p>	
<p>Rev B RELEASE</p>		<p>DWG NO: GS075A-021X REV B</p>	
<p>Revision Record</p>		<p>Title: BATTERY HOLDER CR2032-2</p>	
<p>Revise Only Dn Cod System</p>			

UNIT: mm