



P.C.B. LAYOUT

GS075B - 02 1 X

BATTERY DIM
02:D=19.8mm
T=3.2mm

COLOR: 1:BLACK

PLATING
1:Sn/Pb 90/10 100u" MIN
OVER 30u" MIN NICKEL
G:ROHS

MATERIAL: BODY-FR-NYLON WITH 15% GLASS FILLED
CONTACT(+)-ELECTRODE/PHOSPHOR BRONZE
(-)-ELECTRODE/BRASS

FINISH: CONTACT-TIN 100u" FLASH PLATED OVER NI 30u" UNDER-PLATING

SPECIFICATION
APPLICATION FOR 3V LITHIUM BATTERY
INSULATOR RESISTANCE: 1000M MIN
OPERATION TEMPERATURE: -55°~+105°
DURABILITY: 50 CYCLES MIN
CONTACT RESISTANCE: 30 MI MAX.

UNIT: mm

NOTES
CUSTOMER DRAWING

Global Shine Technology Co., Ltd.
TEL:886-2-8200-3005
FAX:886-2-8200-3014



General Tolerances:		Dim: 0.0	±0.25	Date:	06/10/05	Sheet:	1 OF 1
Angle: ±2°		0.00	±0.20	DWG. NO.:	GS075B-021X	REV:	A
Date:		0.000	±0.10	CHK'd by:			
REV	Revision Record	Date	Appr'd by	Scale	1 : 1		
A	RELEASE	10/07/09					
Revise Only Dn Cod System							

BATTERY HOLDER